# **MACHIM** S-1000 Ceiling Texture

## Aggregated Ceiling Textures

#### Description:

#### S-1000 ceiling textures are white polystyrene aggregated spray textures available in Fine, Medium, and Course grades. They are used for finishing new ceilings and for hiding minor defects in remodel work.

#### Advantages:

- Excellent hide
- Can be painted or left natural white
- Great pattern control
- Easy soap & water cleanup
- Minimal aggregate fallout

#### Available:

- Fine aggregate
- Medium aggregate
- Course aggregate
- 35 lb bag (15.9kg)

#### Coverage:

8.5 sq ft per pound will vary depending on desired look and surface condition.

#### Site Requirements and Storage:

- Maintain 55° F building working temperature until dry
- Keep dry after application
- Above grade application is recommended
- Protect from moisture
- Rotate stock every 90 days

#### Decoration:

Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.

#### Standards:

Meets ASTM C475-89

#### Precautions:

May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children. Ingredient Information: 913-888-0882



P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882

### Submittal Approvals

Job Name:

Contractor:

Date: