

MAGNUM Bond Mine Seal

<p>Description: Magnum Bond is a hand applied Sealant and is composed of inorganic fillers in water based polymeric binder systems fiberglass reinforced. It is designed to be used as a perimeter and void sealant for new and repair work for mine ventilation systems. Approved for dry stacked stoppings, sealing of metal stoppings, dry stacked overcasts, can also be used to seal roof, and ribs.</p> <p>Advantages:</p> <ul style="list-style-type: none">• Can be applied quickly and easily by trowel or rubber gloves• Premixed and ready to use• Quick drying• Excellent workability• Seals against air leaks immediately upon application• Easy clean up• Nonvolatile water based caulking• Noncombustible	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none">• Should not be used in contact with standing or running water• Protect from freezing• Protect from extreme heat• Protect from direct sunlight• Rotate every 9 months• Keep container closed when not in use• Dispose of empty container properly, do not leave underground <p>Coverage: Varies upon condition of surface being sealed</p> <p>Available:</p> <ul style="list-style-type: none">• 3.5 gal. pail (13.1 L) <p>Standards: Meets ASTM E 72-80 Meets ASTM E 162-87 MSHA suitable</p>	<p>Precautions:</p> <p>Avoid contact with skin and eyes. Use with adequate ventilation. Spillage may cause slip hazard, bag for waste, clean with soap and water. Must not be taken internally. Keep out of reach of children. For ingredient information, call 913-888-0882.</p> <p>MAGNUM PRODUCTS</p> <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
---	--	---

Submittal Approvals	
Job Name:	
Contractor:	Date: