




Liteweight Surebond

Setting Type Sandable Joint Compound

<p>Description: Magnum liteweight Surebond is a setting/hardening type compound. Designed for embedding drywall tape, spotting fasteners, filling and leveling cornerbead and patching cracks in plaster walls.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Excellent adhesion • Extremely low shrinkage • Easy sanding qualities • Accurate set times • Reduced tool drag <p>Available set times:</p> <ul style="list-style-type: none"> • 20 minute • 45 minute • 90 minute <p>Available:</p> <ul style="list-style-type: none"> • 18 lb bag (8.2 kg) Lite Weight and MH Formula • 25 lb bag (11.3 kg) Endurance High Strength 	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none"> • Maintain 55° F building working temperature until dry • Do not mix with other materials • Use clean drinking water to mix • Tools must be cleaned between batches • Excessive and high speed mixing will shorten set time • Protect from moisture • New concrete should age 60 days or more before application • Rotate stock every 90 days <p>Decoration: Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Assoc., the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p>Standards: Meets ASTM C475-89</p> <p>Precautions: May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children. Ingredient Information: 913-888-0882</p> <p></p> <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
--	--	---

Submittal Approvals

Job Name:

Contractor:

Date:
