



Interior Drywall Primer/Surfacer

| | | |
|---|---|--|
| <p>Description:</p> <p>Magnum Level Coat is a professional grade, paint underlayment/ primer/surfacer. This vinyl-based product is designed to equalize the porosity or suction differences between the wallboard surface and the drywall joint compound. This allows the paint to dry at a uniform rate, minimizing flashing, banding, and photographing under critical lighting conditions with flat or gloss paints.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Replaces standard priming & skim coating for a level 5 finish • Allows paint to dry uniformly • Paint or decorate in one hour. • Water clean up. • Gives better paint coverage. <p>Coverage:</p> <p>When applied at 15 mil/ wet, one gallon covers approximately 130 square feet.</p> | <p>Available in:</p> <ul style="list-style-type: none"> • 5 gallon pails/18.9 liter--ready-mix • 50 lb bags—dry • 55 gallon drums <p>Site Requirements and Storage:</p> <ul style="list-style-type: none"> • Maintain 50° F building temperature. • Provide adequate mechanical ventilation. • Protect from freezing, extreme heat, direct sunlight. • Rotate stock every 90 days. <p>Preparation:</p> <p>Surfaces must be clean, free of oil, wax, nicotine, and dust. Peeling paint must be removed by sanding, washing, or scraping. Then clean with 1 part household bleach to 3 parts water. Level Coat is not to be used as a sealer.</p> <p>Application:</p> <p>Apply by spray application to interior drywall surfaces only.</p> | <p>Application Caution:</p> <p>Due to the low shrinkage nature of the product, backrolling will leave a “stippled” finish. Extra attention will be necessary to insure the absence of roller marks. Do not over thin. Do not apply when temperature is below 50° F. Wipe up drips or splatter before drying. Contact Magnum before applying over concrete.</p> <p>Standards:</p> <p>Refer to Gypsum Association Publication GA-214, Titled; “Recommended Levels of Gypsum Board Finish” or ASTM C-840. A minimum level 4 drywall finish is recommended before application of Level Coat.</p> <p>Precautions:</p> <p>When sanding, use of a dust collector, eye protection and a NIOSH approved respirator is advisable. Must not be taken internally. If swallowed contact physician. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p> <p>MAGNUM PRODUCTS P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882 www.levelcoat.com</p> |
|---|---|--|

Submittal Approvals

Job Name:

Contractor:

Date:
