




Taping and Topping

All Purpose Ready Mix Joint Compound

<p>Description:</p> <p>Magnum Taping and Topping All Purpose Ready Mix Joint Compound is a professional quality, vinyl based, factory premixed formulation for interior use only. It is designed for embedding drywall tape, spotting fasteners, finishing joints and cornerbead, and the application of simple textures. It can also be used for patching cracks in plaster walls.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Less air than other compounds • Factory premixed • Excellent adhesion • Low shrinkage • More open time/Less tool drag 	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none"> • Maintain 55° F building temperature • Provide adequate mechanical ventilation • Protect from freezing, extreme heat, direct sunlight • Rotate stock each nine months <p>Coverage: 3.5 gallons finishes 450 sq ft of gypsum panels</p> <p>Available:</p> <ul style="list-style-type: none"> • 3.5 gal. boxes (13.1 L) <p>Decoration: Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p>Standards: Meets ASTM C475</p> <p>Precautions: May contain mica, talc, plaster, limestone, perlite, clay and latex. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children. Ingredient Information: 913-888-0882</p> <div style="text-align: center;">  <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p> </div>
--	---	---

Submittal Approvals

Job Name:

Contractor:

Date: