



P.O. Box 15868
15740 W. 108th St.
Lenexa, KS 66285-5868
www.magnum-products.com

Material Safety Data Sheet

Levelcoat P-2002

Section 1 - Product & Company Identification

Product names and codes

Product Name: Magnum Level Coat P-2002

Chemical Family: Aqueous mixture mineral and vinyl acetate polymers.

Product Uses: Interior drywall Level 5 Completion System.

Manufacturer
Magnum Products
15740 W. 108th St.
Lenexa, KS 66219

Emergency Contact Information
Day Phone: (913) 888-0882
Night Phone: (913) 894-2382
Fax: (913) 888-5167

Section 2 – Hazard Identification

Overview

Dry sanding this product creates dust. Eye, skin, nose, throat and upper respiratory irritation can occur with prolonged dust exposure. Minute amounts of vinyl acetate monomer vapors are released from these products which may be trapped by the packaging. When packaging is opened the trapped vapors escape and dissipate quickly. This is more likely to occur in products packaged in pails.

Potential Acute effects of exposure to products

Eyes: Dust/mist/vapors can cause mechanical irritation to the eyes. If burning, redness, itching, pain or other symptoms persist contact a physician. Acrylic polymer vapors may cause slight temporary eye irritation. Ethylene glycol vapors may cause slight temporary eye irritation.

Skin: Direct contact may cause irritation, rash or dry skin. Rubbing may intensify symptoms and create abrasions.

Ingestion: None known

Inhalation: Exposure to dust, mist or vapors generated during the handling, spray application or use of the product may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory tract. Persons subjected to large amounts of this dust, mist or vapor will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician. Breathing of acrylic polymer and/or ethylene glycol vapors can cause slight headache, dizziness, nausea, drowsiness



Material Safety Data Sheet

Levelcoat P-2002

Page 2 of 9

and/or stupor. Exposure to high vapor levels of either or both of these may irritate the nose, throat, or upper respiratory tract. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.

Potential Chronic effects of exposure to products

Eyes: None known

Skin: None known

Ingestion: None known

Inhalation: This product may contain small amounts of vinyl acetate monomer, vapors of which can cause tumors in the respiratory tract of test animals at very high levels over a lifetime. Overexposure is not expected to occur during normal usage of this product. No tumors have been observed in animals exposed to 50 ppm or below the TLV. Exposure to respirable crystalline silica might be possible during the normal use of this product. Actual exposure levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e. silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration. Prolonged and repeated breathing of respirable mica dust may cause lung disease (pneumoconiosis). The extent and severity of lung injury correlates with the length of exposure and dust concentration. Animal studies indicate that prolonged and repeated overexposure to ethylene glycol may cause kidney and/or liver damage and birth defects. Overexposure is highly unlikely at concentrations present in this product.

Section 3 – Composition/Information on Ingredients

Component	CAS Number	PEL mg/m ³	TLV mg/m ³	WT %
Tributyltin benzoate solution				
2(9hydroxymethyl amino) ethanol	CAS# 34375-28-5	N/E	N/E	<0.1
Calcium Carbonate	CAS# 1317-65-3	15/5 (R)	10	>45
Perlite	CAS# 93763-70-3	15	10 (R)	>4
Vinyl Acetate Polymer	CAS# 24937-78-8	N/E	N/E	<5
Mica	CAS# 12001-26-2	20 mppcf	3 (R)	<7
Talc	CAS# 14807-96-6	20 mppcf	2 (R)	
Starch	CAS# 9005-25-8	5	N/E	
Titanium Dioxide	CAS# 13463-67-7	10/5 (R)	#	
Hydroxyethylcellulose	CAS# 9004-62-4	N/E	N/E	
Hydroxypropylmethylcellulose	CAS# 9004-65-3	N/E	N/E	
Polyvinyl alcohol	CAS# 9002-89-5	N/E	N/E	
Attapulgitte Clay	CAS# 12174-11-7	N/E	N/E	<5
Crystalline Silica*	CAS# 14808-60-7	15	10	<2
Vinyl Acetate Monomer	CAS# 108-05-4	10ppm	10ppm	<0.1

*as a natural occurring constituent

(R) Respirable Dust; N/E Not Established



Crystalline Silica- The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance, which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.

All ingredients of this product are included in the U.S, Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory. All components of this product are included in the Canadian Domestic Substance List (DSL) or the Canadian Non-Domestic Substances List (NDSL).

Section 4 – First Aid Measures

Eyes: Wash immediately with water (30 minutes) seek medical attention to avoid lasting effect. Do not rub eyes. Remove contact lenses.

Skin: Remove clothing from affected area. Rinse skin with water, then wash with soap and water, if rash occurs discontinue use and see physician. Wash clothing before reuse.

Ingestion: No effects expected. Seek medical attention if problems develop. Not intended for ingestion. If swallowed, do not induce vomiting. Give large quantities of water, or if available several glasses of milk. If vomiting occurs spontaneously, keep airway passage clear and give more water.

Inhalation: Remove from area of dust exposure to fresh air until symptoms subside. If necessary seek medical attention.

Target Organs: Eyes, Skin, Respiratory System.

Medical conditions which may be aggravated: Pre-existing upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

Primary route of entry: Inhalation, eyes, and contact with skin.

Section 5 – Fire Fighting Measures

Hazardous Combustible Products: None known

Flash Point: Not applicable, Semi-liquid, non-combustible.

Extinguishing Media: Water or use extinguishing media appropriate for surrounding fire.

Flammable Limits: Not determined.

Special Fire Fighting Procedures: Wear appropriate personal protective equipment. See Section 8.

Unusual Fire and Explosion Hazards: None known.

Special Fire Fighting Protective Equipment: Not applicable

Flammable Properties: Not flammable or combustible. NFPA Hazard Class No: 1/0/0.

Section 6 – Accidental Release Measures

Spill Procedure: Slippery when wet, bag for disposal, wash area with water.

Landfill: In accordance with Local, State and Federal Regulations. Never discharge directly into sewers or surface waters. Wear appropriate personal protective equipment. Maintain proper ventilation to minimize dust.

Section 7 – Handling and Storage

- Keep away from children.
- Keep dry, do not store in direct sunlight.
- Store at 60-95°F (15-35° C)
- Rotate Stock every 90 days.
- Do not mix with other products.
- Do not reuse empty containers.
- Discard empty containers in accordance with Local, State and Federal Regulations.
- Avoid contact with eyes, skin and clothing.
- Wear appropriate protective equipment (see Sec. 8).
- Minimize generation of dust.
- Avoid breathing dust or vapors.
- Keep from freezing to preserve usefulness.
- Keep containers closed when not in use

Section 8 – Exposure Controls/Personal Protection

Exposure guidelines: Exposure limits may be found in Section 3 – Composition/Information on ingredients.



Material Safety Data Sheet

Levelcoat P-2002

Page 5 of 9

Component	CAS Number	PEL mg/m ³	TLV mg/m ³	WT %
Tributyltin benzoate solution				
2(9hydroxymethol amino) ethanol	CAS# 34375-28-5	N/E	N/E	<0.1
Calcium Carbonate	CAS# 1317-65-3	15/5 (R)	10	>45
Perlite	CAS# 93763-70-3	15	10 (R)	>4
Vinyl Acetate Polymer	CAS# 24937-78-8	N/E	N/E	<5
Mica	CAS# 12001-26-2	20 mppcf	3 (R)	<7
Talc	CAS# 14807-96-6	20 mppcf	2 (R)	
Starch	CAS# 9005-25-8	5	N/E	
Titanium Dioxide	CAS# 13463-67-7	10/5 (R)	#	
Hydroxyethylcellulose	CAS# 9004-62-4	N/E	N/E	
Hydroxypropylmethylcellulose	CAS# 9004-65-3	N/E	N/E	
Polyvinyl alchohol	CAS# 9002-89-5	N/E	N/E	
Attapulgate Clay	CAS# 12174-11-7	N/E	N/E	<5
Crystalline Silica*	CAS# 14808-60-7	15	10	<2
Vinyl Acetate Monomer	CAS# 108-05-4	10ppm	10ppm	<0.1

T = Total; R = Respirable; N/E = Not Established; C = Ceiling; STEL = Short-term exposure limit;
F = Fume; Du = Dust; M = Mist; ppm = part per million; f/cc = fiber per cubic centimer;
Mppcf = million particles per cubic foot.

Engineering Controls: Provide adequate local and general exhaust ventilation to minimize dust and keep exposure below the TLV limits. Wet sand when ever possible. See "Finishing and Decorating Gypsum panels Wet Sanding J-6101/12-87".

Personal Protective Equipment (PPE)

PPE Eyes/Face: Wear eye goggles or safety glasses for protection from dust. Comply with OSHA's PPE standards 29 CFR 1910.132 and 133 for eye and face protection.

PPE Skin: Wear protective gloves to prevent dry and itchy skin. Comply with 29 CFR 1910.132 (general) and 138 (hand protection).

PPE Respiratory: Wear NIOSH/MSHA approved respirator equipped with particulate cartridges when dry sanding or spraying material or if TLV is exceeded. Since job conditions vary, respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Section 9 – Physical and Chemical Properties

Appearance: Off white Semi-liquid
Physical State: Semi-liquid
Vapor Pressure: Not applicable
Boiling Point: 212 degrees Fahrenheit
Solubility: 1.5-2.0
Partition Coefficient: Not Determined
Auto-ignition Temp: Not Determined
Decomposition Temp: Not Determined
Flash Point: Not Applicable
Upper Flammable Limit (UFL): Not Determined
Molecular Weight: Mixture
Freezing Point: 32°F/0°C

Odor: Mild acetate odor
PH: 8.0-8.5
Vapor Density: <1 same as water
Melting Point: Not applicable
Specific Gravity: 1.3-2.5
Flammability: Not Determined
VOC content: <2g/l
Viscosity: Not Determined
Evaporation rate: Not Applicable
Lower Flammable Limit (LFL): Not Determined
Bulk Density: 12-13 lbs/gal
Evaporation Rate (BuAc = 1): <1 same as water

Section 10 – Stability and Reactivity

- **Chemical Stability:** Stable
- **Conditions to avoid:**
 - Contact with strong acids
 - High temperatures cause decomposition (see below)
 - Do not allow product to freeze
- **Incompatibility:** Strong acids
- **Hazardous Polymerization:** Will not occur.
- **Hazardous Decomposition:** Thermal decomposition may yield acrylic monomers, carbon dioxide and carbon monoxide.

Section 11 – Toxicological Information

Crystalline Silica: the International Agency for Research on Cancer (IARC) states that crystalline silica inhaled in the form of quartz or cristolbalite from occupational sources is carcinogenic to humans (group 1). The IARC noted that carcinogenicity in humans was not detected in all industrial circumstances studies. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen. The weight percent of respirable crystalline silica may not have been measured in this product. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. Smoking in combination with silica exposures increases the risk of cancer. The risk of developing silicosis is dependent upon the exposure intensity and duration. Prolonged exposure to respirable crystalline silica has been known to cause silicosis. The risk of contracting silicosis is multiplied by the amounts of respirable silica you

are exposed to and the length of time you are exposed to it. Certain people may be more susceptible than others.

Mica: Prolonged and repeated breathing of respirable mica dust may cause lung disease (pneumoconiosis). The extent and severity of lung injury correlates with the length of exposure and dust concentration.

Some products may contain attapulgite clay. IRC classifies attapulgite (long fiber) carcinogenic to humans, Group 2B. Attapulgite is not classified as a carcinogen by NTP or OSHA.

Section 12 – Ecological Information

This product has no known adverse effect on ecology nor presents an ecological hazard to the environment.

Environmental Fate: no known effects

Aquatic Toxicity: no known effects

Environmental Toxicity: non known effects

Ecotoxicity value: Not Determined

Section 13 – Disposal Considerations

Disposal Instructions: Dispose of as inert solid in landfill. Dispose of waste material according to Local, State and Federal environmental regulations. Never discharge directly into sewers or surface waters.

General product information: Disposed of as supplied is not considered a hazardous waste under Federal Hazardous Waste Regulations 40 CFR 261. If processing, use, or contamination alters the material the waste must be tested using methods described in 40 CFR 261 to determine if it meets applicable definitions of hazardous wastes.

Component waste numbers: not applicable

Section 14 – Transportation Information

- This material is not a DOT hazardous material
- Hazard class: Not classified
- ICAO/IATA/IMO: Not applicable
- Shipping Name: Same as product name
- UN/NA #: None. Not classified
- Packing Group: None
- GGVSec/MDG-Cod: Not classified
- RID/ADR: None
- ADNR: None



Section 15 – Regulatory Information

All ingredients are included on the TSCA inventory.

United States Federal Regulations

General Product Information: Dust and potential respirable crystalline silica generated from cutting, sanding or otherwise machining this product may be hazardous.

Component analysis: This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLs (40 CFR 302.4)

OSHA: Dust and potential respirable crystalline silica generated from mixing, sanding or otherwise using this product may be hazardous.

RSCA: If discarded as supplied, this product would not be a hazardous waste. Under RCRA, however, it is the responsibility of the product user to determine at the time of disposal whether a material containing this product or derived from this product should be classified as a hazardous waste.

TSCA: This product complies with TSCA inventory requirements.

SARA 313: None.

Key:

SARA Title III Section 302 (EPCRA) Extremely Hazardous Substances: Threshold Planning Quantity (TPQ)

SARA Title III Section 304 (EPCRA) Extremely Hazardous Substances: Reportable Quantity (RQ)

SARA Title III Section 313 (EPCRA) Toxic Chemicals: X=Subject to reporting under section 313

CERCLA Hazardous Substances: Reportable Quantity (RQ)

CAA Section 112 (r) Regulated Chemicals for Accidental Release Prevention: Threshold Quantities (TQ)

RCRA Hazardous Waste: RCRA hazardous waste code.

State Regulations

California Prop 65: This product contains small amounts of naturally occurring crystalline silica. This element is known to the State of California to cause cancer.

Canada WHMIS

This product is not a controlled product. This product has been classified in accordance with the hazard criteria of Controlled Product regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16 – Other Information

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It may not be valid for this material if it is used in combination with any other material. It is offered for your consideration, investigation, and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Magnum Products makes no warranties of any kind, expressed or implied, concerning the accuracy of completeness of the information and data herein. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded. Magnum Products will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading. This material safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 DFR 1910.1200) and with the Workplace Hazardous materials Information System (WHMIS).

Key/Legend

ACGIH	American Conference of Governmental Industrial Hygienists
ANSI	American National Standards Institute
CAA	Clean Air Act
CAS	Chemical Abstracts Service (Registry Number)
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act of 1980
CFR	Code of Federal Regulations
DOT	Department of Transportation
DSL	Canadian Domestic Substances List
EPA	United States Department of Transportation
EPCRA	Emergency Planning & community right-to-know Act
HEPA	High Efficiency Particulate Air
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMO	International Maritime Organization
MSHA	Mine Safety and Health Administration
NDSL	Canadian Non-Domestic Substances List
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Health and Safety Administration
PEL	Permissible Exposure Limit
PPE	Personal Protection Equipment
RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act of 1986
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
UN/NA#	United Nations/North America number
WHMIS	Workplace Hazardous Material Information System