


MAGNUM Green Topping

Ready Mix Joint Compound

<p>Description:</p> <p>Magnum Ready Mix Topping Compound is a professional quality, vinyl based, factory premixed formulation. It is designed to be used as a fill and finish coat joint compound. It should NOT be used to embed drywall tape or as a first coat over cornerbead. Its great workability and shrinkage factors make it excellent for finishing joints, spotting fasteners, and as a finishing coat over cornerbead.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Less air than other compounds • Factory premixed • Low shrinkage • Ease of sanding • More open time/Less tool drag 	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none"> • Maintain 55° F building working temperature until dry • Protect from freezing, extreme heat, direct sunlight • Rotate stock each nine months <p>Coverage:</p> <p>125-150 lbs. covers 1000 sq ft of gypsum panel</p> <p>Available:</p> <ul style="list-style-type: none"> • 50 lb cartons (22.7kg) • 62 lb pail (28.1kg) • 13 lb pail (1 gallon) <p>Decoration:</p> <p>Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p>Standards:</p> <p>Meets ASTM C475-89</p> <p>Precautions:</p> <p>May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p> <div style="text-align: center;">  <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p> </div>
---	--	--