




# FJS -767 Super FLEX

## Taping Flexible R/M Joint Compound

<p><b>Description:</b></p> <p>Magnum Super Flex Joint Taping Compound is a highly unique, flexible vinyl based premixed formulation. It is designed to minimize drywall joint cracks caused by structural movement or wood framing expansion / construction. Super Flex is to be used for embedding drywall tape, and first coat over fasteners and drywall trims. Use on interior wallboard surfaces only.</p> <p><b>Extreme Flexibility/Strength Advantages:</b></p> <ul style="list-style-type: none"><li>• Super Elastomeric when dry</li><li>• Less air than other compounds</li><li>• Factory Premixed</li><li>• Excellent adhesion</li><li>• Low shrinkage</li><li>• More open time/Less tool drag</li><li>• Super Strong, Flexible Joints</li><li>• Hand Apply</li></ul>	<p><b>Site Requirements and Storage:</b></p> <ul style="list-style-type: none"><li>• Maintain 55° F building temperature</li><li>• Provide adequate mechanical ventilation</li><li>• Protect from freezing, extreme heat, direct sunlight</li><li>• Rotate stock every 90 days</li></ul> <p><b>Coverage:</b></p> <p>Approx 1 pail per 1000 sq ft of gypsum panel</p> <p><b>Available:</b></p> <ul style="list-style-type: none"><li>• 4.5 gallon (17.1L) plastic pail</li></ul> <p><b>Decoration:</b></p> <p>Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and Association Wall and Ceiling Industries.</p>	<p><b>Standards:</b></p> <p>Meets ASTM C475-89. FJS-727 Taping is part 1 of Magnum's Flexible Ready mix system and is to be used in conjunction with Magnum FJS-757 Filling Compound and then finished with any of Magnum's other Ready Mixed Compounds.</p> <p><b>Precautions:</b></p> <p>May contain mica, talc, limestone, perlite, clay and latex. Caution: sanding is not possible due to the highly flexible and elastomeric nature of this product. Must not be taken internally. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p> <p></p> <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
--	---	---