

Material Safety Data Sheet

page 1 of 3

MSDS-FJS-727 and FJS-757 Flexible Ready Mix Joint Compound FJS-767 Super Flex Ready Mix Joint Compound

Section I- Manufacturer

Magnum Products 15740 West 108th Lenexa, KS 66219	Emergency Telephone: Day: 913-888-0882 Night: 913-894-2382	Trade Name: Magnum Flex Joint Compound FJS-727 Taping ,FJS-757 Filling, Chemical name N/A
---	---	--

Section II - Hazardous Ingredients

		PEL mg/m ³	TLV mg/m ³
2 {(hydroxymethyl) amino} ethanol	CAS# 34375-28-5	N/E	N/E
Polyvinyl Alcohol	CAS# 9002-89-5	N/E	N/E
Plaster of Paris	CAS# 26499-65-0	15/5(R)	10
Calcium Carbonate	CAS# 1317-65-3	15/5(R)	10
Perlite	CAS# 93763-70-3	15	10(R)
Polyvinyl Acetate	CAS# 9003-20-7	N/E	N/E
Vinyl Acetate Monomer	CAS# 108-05-4	10	35
Mica	CAS# 12001-26-2	20mppcf	3(R)
Attupulgite	CAS# 1332-58-7	15	10
Quartz*	CAS# 14808-60-7	10	10

* as a natural occurring constituent

(R) Respirable Dust (NE) Not Established

Section III - Physical / Chemical Characteristics

<i>Appearance & Odor</i>	Off White-semi liquid with mild acetate odor.
<i>pH</i>	8.0 to 9.5
<i>Percent Volatile by Volume</i>	Approx. 35% VOC < 20 grams per liter.

Material Safety Data Sheet

continued page 2 of 3

MSDS-FJS-727 and FJS-757 Flexible Ready Mix Joint Compound FJS-767 Super Flex Ready Mix Joint Compound

Section IV - Fire & Explosion Hazard Data

<i>Flash point</i>	N/A Semi Liquid, non combustible
<i>Special Firefighting procedures</i>	None

Section V - Reactivity Data

<i>Stable</i>	CO2 released when heated to decomposition.
<i>Hazardous Polymerization</i>	Will not occur.

Section VI - Health Hazard Data

	ACUTE	CHRONIC
<i>Eye Contact</i>	Irritation	None Known
<i>Ingestion</i>	None Known	None Known
<i>Inhalation</i>	Sanding dust or spray mist may irritate the eyes, nose throat, and upper respiratory system. Mild respiratory irritant	Long term inhalation of large quantities of respirable mica dust or vinyl acetate monomer can cause lung damage (pulmonary fibrosis)
<i>Skin Contact</i>	May cause rash or dry skin	None Known

EMERGENCY AND FIRST AID PROCEDURES

<i>Eye Contact</i>	Wash immediately with water (15 minutes) seek medical attention to avoid lasting effects
<i>Skin Contact</i>	Remove clothing from affected area, wash skin with soap and water, if rash occurs discontinue use, see physician. Wash clothing before reuse.
<i>Inhalation</i>	Move to fresh air.
<i>Ingestion</i>	If conscious, drink water, see physician.

Material Safety Data Sheet

continued page 3 of 3

MSDS-FJS-727 and FJS-757 Flexible Ready Mix Joint Compound FJS-767 Super Flex Ready Mix Joint Compound

TARGET ORGANS Lungs.

Medical conditions which may be aggravated: Pre-existing upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

Primary Route of entry: Inhalation.

Section VII - Safe Handling & Use

Spill procedure Slippery when wet, bag for disposal, wash area with water.

Landfill In accordance with regulations.

Section VIII - Control Measures

Special Precaution Use respirator device when dry sanding (OSHA/MSHA approved). Wet sand if at all possible.

Eye Protection Goggles if dusty.

Handling & Storage Protect from freezing & direct sunlight.

CAUTION

Keep out of reach of children. If ingested give conscious person water, never give an unconscious person fluid, material is non-toxic, consult physician. Protect eyes during application and sanding, if irritation occurs flush for 15 minutes consult physician. Wet sand if at all possible, if dry sanding wear (NIOSH/MSHA) approved respirator. Dust may cause eye, nose throat or upper respiratory irritation, long term breathing of large amounts of mica may cause lung disease.