


MAGNUM R-700 Taping

Ready Mix Joint Compound

<p>Description:</p> <p>Magnum Ready Mix Taping Compound is a professional quality, vinyl based, factory premixed formulation. It is designed to be used for embedding drywall tape. Its excellent adhesion and extended open time make it excellent for the job it is designed for.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Excellent adhesion • Factory premixed • Extended open time • Better mileage per unit 	<p>Site Requirements and Storage:</p> <ul style="list-style-type: none"> • Maintain 55° F building working temperature until dry • Protect from freezing, extreme heat, direct sunlight • Rotate stock every 90 days <p>Coverage:</p> <p>175 lbs. covers 1000 sq ft of gypsum panel</p> <p>Available:</p> <ul style="list-style-type: none"> • 50 lb cartons (22.7kg) • 62 lb pail (28.1kg) <p>Decoration:</p> <p>Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Association, The Painting and Decorating Contractors of America, the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p>Standards:</p> <p>Meets ASTM C475-89</p> <p>Precautions:</p> <p>May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p>  <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
--	--	---