

MSDS-Primer & Primer Sealer

Section I- Manufacturer

Magnum Products 15740 West 108th Lenexa, KS 66219	Emergency Telephone: Day: 913-888-0882 Night: 913-894-2382	Trade Name: Magnum Drywall Textures Magnum Primer/Sealer, Primer. Chemical Family: Latex Based Paint.
---	---	--

Section II - Hazardous Ingredients

		PEL mg/m³	TLV mg/m³
Ethylene Glycol			
Titanium Dioxide	CAS # 107-21 -1	125 mg/cu M.	125 mg/cu M.
Quartz*	CAS # 13463-67-7	.1 mg/cu M.	.1 mg/cu M.
*as a natural occurring constituent	CAS # 14808-60-7	.1 mg/cu M	.1 mg/cu M

Section III - Physical / Chemical Characteristics

<i>Appearance</i>	White Liquid.
<i>Odor</i>	Mild Ammonia Odor
<i>Weight</i>	11 lb/gal. - Primer/Sealer · 10 lb/gal. - Primer

Section IV - Fire & Explosion Hazard Data

<i>Flash point</i>	None
<i>Extinguishing Media</i>	Will not burn.
<i>Unusual Fire and Explosion Hazards</i>	None
<i>Special Firefighting Procedures</i>	None known.

Section V - First Aid And Emergency Procedures

page 2 of 3

<i>Swallowing</i>	If swallowed, give 1-2 glasses of water to drink and call a physician immediately.
<i>Inhalation</i>	Remove to fresh air.
<i>Eyes</i>	Flush thoroughly with water for 15 minutes, contact a physician.
<i>Skin</i>	Wash affected area with soap and water, seek medical attention if irritation persists.

Section VI - Reactivity Data

<i>Stability</i>	Stable.
<i>Incompatibility (materials to avoid)</i>	None.
<i>Hazardous Decomposition Products</i>	Burning will produce carbon monoxide and carbon dioxide.
<i>Hazardous Polymerization</i>	Will not occur.
<i>Conditions to Avoid</i>	None known.

Section VII - Environmental Information

Steps to be taken in case material is released or spilled:

1. Use absorbent material to clean up.
2. Place in container for proper disposal.

<i>Waste Disposal</i>	Disposal in accordance with Federal, State, and Local regulations.
<i>RCRA Classification</i>	If discarded as is, it is not classified as a hazardous waste under RCRA.
<i>Environmental Hazards</i>	Not Known.

Section VIII - Personal Protection Information

page 3 of 3

<i>Respiratory Protection</i>	Use appropriate, properly fitted NIOSH/MSHA approved respirator
<i>Ventilation</i>	Provide local exhaust ventilation as to maintain exposure below nuisance dust limits and permissible exposure.
<i>Protective Equipment</i>	Safety glasses and rubber (neoprene) gloves are recommended.

Section IX - Special Precautions

Protect from freezing and extremely high temperatures.
Keep away from children.
Close container after each use.