

# **MAGNUM** Liteweight Surebond Ready Mix Joint Compound

<p><b>Description:</b></p> <p>Magnum liteweight Surebond is a setting/hardening type compound. Designed for embedding drywall tape, spotting fasteners, filling and leveling cornerbead and patching cracks in plaster walls.</p> <p><b>Advantages:</b></p> <ul style="list-style-type: none"> <li>• Excellent adhesion</li> <li>• Extremely low shrinkage</li> <li>• Easy sanding qualities</li> <li>• Accurate set times</li> <li>• Reduce tool drag</li> </ul> <p><b>Available set times:</b></p> <ul style="list-style-type: none"> <li>• 20 minute</li> <li>• 45 minute</li> <li>• 90 minute</li> </ul> <p><b>Available:</b></p> <ul style="list-style-type: none"> <li>• 18 lb bag (8.2 kg)</li> <li>• 25 lb. bag (11.3 kg) Endurance High Strength</li> </ul>	<p><b>Site Requirements and Storage:</b></p> <ul style="list-style-type: none"> <li>• Maintain 55° F building working temperature until dry</li> <li>• Do not mix with other materials</li> <li>• Use clean drinking water to mix</li> <li>• Tools must be cleaned between batches</li> <li>• Excessive and high speed mixing will shorten set time</li> <li>• Protect from moisture</li> <li>• New concentrate should age 60 days or more before application</li> <li>• Rotate stock every 90 days</li> </ul> <p><b>Decoration:</b></p> <p>Final wallboard finish should comply with the Five Levels of Gypsum Board Finish approved by the Gypsum Assoc., the Drywall Finishing Council, and The Association of Wall and Ceiling Industries.</p>	<p><b>Standards:</b></p> <p>Meets ASTM C475-89</p> <p><b>Precautions:</b></p> <p>May contain mica, talc, plaster, limestone, perlite, clay and latex. Wet sanding is advisable to avoid creating dust. When dry sanding, use of a dust collector, eye protection, and a respirator approved by NIOSH to remove dust is advisable. Must not be taken internally. Keep Out Of Reach Of Children.</p> <p>Ingredient Information: 913-888-0882</p> <p><b>MAGNUM</b> PRODUCTS</p> <p>P.O. BOX 15868 LENEXA, KS 66285-5868 (913) 888-0882</p>
--	--	---